ON/OFF TOOL

The **D&L On/Off Tool** is a fully machined, weld-free tubing seal receptacle allowing isolation of a lower zone using a wireline blanking plug. The tubing string can then be removed from the well. When re-run, the tubing string automatically re-engages to the stinger, and the blanking plug can be retrieved by wireline.

The **D&L On/Off Tool** is run above an ASI-X Packer, a VSI-X Packer or a Permapak Seal Bore Packer with a latch seal mandrel.

The **D&L On/Off Tool** is fully compatible with D&L's existing DT-2 Stingers and On/Off Tool Top Subs. Utilizing a common J-body among all casing sizes (per connection / stinger size) translates to less inventory items for customers to stock. Interchangeable milling shoes are available in all casing sizes to quickly and easily convert from one size to another.

Special Features:

- >Fully integral design
- >Compatible with most T-2 tools
- >Common J-body

		1	
			l
,	5		
1			

Stinger Size (Pin Down)	Tool Thread Connection (Box Up)	Casing Size (inches)	Shoe OD (In.)
1.050	1.900	2-7/8	2.250
1.030	1.900	3-1/2 (12.95#)	2.500
1.900 NUE	1.900	3-1/2	2.750
		4	3.250
1.900 EUE	1.900	4-1/2 (18.8#)	3.437
		4-1/2 (15.1 - 16.9#)	3.580



ENVISION DOWNHOLE, LLC

801 S. Pagewood Ave. Suite 7 Odessa, TX 79761 T: 432-217-8644 | envisiondownhole.com





