

# TM ANCHOR/CATCHER

The TM Anchor/Catcher is a retrievable positive action anchor tool to hold tubing strings in tension or compression during pump strokes to prevent tubing buckling. This increases pumping efficiency while reducing rod and tubing wear. This tool also catches the tubing should it part. Stainless steel drag springs employ low stress value to minimize failure under corrosive conditions. If the TM Anchor/Catcher cannot be released with right-hand rotation, it is equipped with a shear release activated by an upward pull.

## Special Features:

- Stainless steel drag springs
- Enclosed slips
- Rotation or shear release
- Safety release valve easily adjusted

## Product Specifications:

Casing		Recommended Hole Size (inches)	Tool OD (inches)	Tool ID (inches)	Thread Connections Box Up / Pin Down
Size (inches)	Weight (lbs/ft)				
4-1/2	9.5 - 13.5	3.920 - 4.090	3.750	2.00	2-3/8 EUE
	13.5 - 15.1	3.826 - 3.920	3.656	2.00	2-3/8 EUE
5-1/2	13.0 - 23.0	4.670 - 5.044	4.500	2.00	2-3/8 EUE
				2.38	2-7/8 EUE
6-5/8	20.0 - 32.0	5.675 - 6.049	5.500	2.50	2-7/8 EUE
				3.00	3-1/2 EUE
7	17.0 - 32.0	6.094 - 6.538	5.875	2.00	2-3/8 EUE
				2.50	2-7/8 EUE
				3.00	3-1/2 EUE
7-5/8	24.0 - 39.0	6.625 - 7.025	6.400	2.50	2-7/8 EUE
9-5/8	32.3 - 53.5	8.535 - 9.001	8.250	3.00	3-1/2 EUE
				4.00	4-1/2 EUE



## ENVISION DOWNHOLE, LLC

801 S. Pagewood Ave. Suite 7 Odessa, TX 79761

T: 432-217-8644 | [envisiondownhole.com](http://envisiondownhole.com)

