PERMANENT HYD ISOLATION PACKER

The Permanent Hydraulic Isolation Packer is a robust production packer capable of handling large amounts of weight hung below the packer. This packer features a large ID for increased flow potential. This packer also has upper and lower centralizing slips which increases its ability to set in deviated sections of wells. This packer uses our proven Permapak components.

The setting equipment for the Permanent Hydraulic Isolation Packer is built into the packer. It requires pressurizing the tubing/casing it is run on once the packer reaches setting depth.

Special Features:

>Adjustable setting pressure >Utilizes Permapak components

Product Specifications:

Casing		Recommende	Tool OD	Packer	Thread
Size (inches)	Weight (lbs/ft)	d Hole Size (inches)	(inches)	Bore (inches)	Connections Box Up / Pin Down
7	17.0 - 26.0	6.276 - 6.538	6.000	4.000	4-1/2 LTC
					4-1/2 BTC
	23.0 - 32.0	6.094 - 6.366	5.875	4.000	4-1/2 LTC
					4-1/2 BTC
7-5/8	24.0 - 39.0	6.625 - 7.025	6.250	4.000	4-1/2 LTC
					4-1/2 BTC
9-5/8	36.0 - 53.5	8.535 - 8.921	8.125	5.000	5-1/2 LTC
				5.500	6-5/8 LTC
				6.000	7" LTC

ENVISION DOWNHOLE, LLC

801 S. Pagewood Ave. Suite 7 Odessa, TX 79761 T: 432-217-8644 | envisiondownhole.com

