

# SNAPSET I PACKER

The **Snapset I Packer** is a compression set packer requiring only straight set down weight to pack-off. This packer is run above other packers (such as the ASI-X Packer, AS-II Packer or AS-III Packer) for selective production to isolate casing holes and perforations.

This packer has no upper or lower slips and should be used only where intermediate differential pressures from below are expected. This packer has an internal

latch to prevent the packer from setting prematurely when running down the hole. When releasing, the latch re-engages to allow movement downhole and re-setting.

## Special Features:

- >Large internal by-pass
- >Set down to pack-off, pick up to release
- >Short compact design

## Product Specifications:

Casing		Recommended Hole Size (inches)	Tool OD (inches)	Tool ID (inches)	Thread Connections Box Up / Pin Down
Size (inches)	Weight (lbs/ft)				
3-1/2	7.7 - 10.2	2.922 - 3.068	2.781	1.25	1.900 NUE
4-1/2	9.5 - 13.5	3.920 - 4.090	3.750	1.94	2-3/8 EUE
5-1/2	14.0 - 20.0	4.778 - 5.012	4.625	2.00	2-3/8 EUE
				2.38	2-7/8 EUE
	20.0 - 23.0	4.670 - 4.778	4.500	2.00	2-3/8 EUE
				2.38	2-7/8 EUE
7	17.0 - 26.0	6.276 - 6.538	6.000	2.50	2-7/8 EUE
	26.0 - 32.0	6.094 - 6.276	5.875	2.50	2-7/8 EUE
7-5/8	24.0 - 29.7	6.875 - 7.025	6.672	2.50	2-7/8 EUE
9-5/8	43.5 - 53.5	8.535 - 8.755	8.250	3.00	3-1/2 EUE



## ENVISION DOWNHOLE, LLC

801 S. Pagewood Ave. Suite 7 Odessa, TX 79761

T: 432-217-8644 | [envisiondownhole.com](http://envisiondownhole.com)

