

# CR BRIDGE PLUG

The **CR Bridge Plug** provides the end user with tools that will consistently contain well pressures at elevated temperatures and pressures. This plug permits faster removal from the well with either rotary or cable tool methods due to its compact size and the selection of high quality construction material.

The short, compact, interlocked construction assures the user that the CR Bridge Plug will provide faster, safer run-in, dependable set and pack-off and hold pressure that is safe for the casing weight and grade. The interlock construction and compact size requires minimal material removal during drill out. The outside diameter of these products has been held to a minimum to provide maximum tool-to-casing clearance for

safe running and maximum fluid by-pass area during displacement procedures even in heavy mud systems.

A Wireline Adapter Kit (WLAK) and Hydraulic Setting Tool are used for setting CR Bridge Plugs.

**NOTE:** The CR Bridge Plug is designed to provide a temporary wellbore seal. For a permanent wellbore seal, cement must be set on top of the plug.

## Special Features

- >Can be converted to cement retainer
- >Can be set mechanically or wireline set.

## Product Specifications

Casing		Recommended Hole Size (inches)	Tool OD (inches)
Size (inches)	Weight (lbs/ft)		
4-1/2	9.5 - 15.1	3.826 - 4.090	3.612
5	11.5 - 18.0	4.276 - 4.560	3.937
5-1/2	14.0 - 23.0	4.670 - 5.012	4.315
6-5/8	17.0 - 32.0	5.675 - 6.135	5.375
7	17.0 - 35.0	6.004 - 6.538	5.680
7-5/8	20.0 - 39.0	6.625 - 7.125	6.313
8-5/8	24.0 - 52.0	7.435 - 8.097	7.125
9-5/8	29.3 - 58.4	8.435 - 9.063	8.125
10-3/4	32.75 - 60.7	9.660 - 10.192	9.437
11-3/4	38.0 - 60.0	10.772 - 11.150	10.437
13-3/8	48.0 - 72.0	12.347 - 12.715	12.000

### ENVISION DOWNHOLE, LLC

801 S. Pagewood Ave. Suite 7 Odessa, TX 79761

T: 432-217-8644 | [envisiondownhole.com](http://envisiondownhole.com)



Mechanical

Slip Kit

