

EXTERNAL DIMPLE CONNECTOR

The External Dimple Connector was designed to attach the BHA to the end of the coil.

The Dimple Connector is secured to the outside of the coiled tubing by a series of set screws that seat a pattern of impressions created with a special design dimpling tool.



Features:

- >Quick redress
- >High torque and tensile applications
- >Used for drilling, milling and fracking
- >Slimline applications

Product Specifications:

Coil Size	1 ½"	1 ¾"	2"	2 3/8"	2 5/8"	2 7/8"
Tool OD (in)	2.125	2.250	2.875	2.875	3.625	3.875
Connections	1 ½" AMMT	1 ½" AMMT	2 ¾" PAC	2 ¾" PAC	2 ¾" PAC	2 ¾" REG
Tensile Strength (lbs)	107,000	81,000	120,000	140,000	200,000	324,000
Torsional Strength (ft/lbs)	1,600	1,600	4,000	4,000	4,000	5,810
ID (in)	1.000	1.000	1.375	1.375	1.375	1.000
Length (in)	8.000	7.000	7.750	9.125	9.125	8.500
Working Pressure (psi)	8,000	8,000	8,000	8,000	8,000	10,000

ENVISION DOWNHOLE, LLC

801 S. Pagewood Ave. Suite 7 Odessa, TX 79761

T: 432-217-8644 | envisiondownhole.com

